

# MULTI-CAMERA POWER SUPPLIES

## AC & DC 4, 8, & 16 Outputs

### Product Features

- Up to 400 VA 115 VAC input (220 VAC input available).
- 24 VAC outputs: up to 2 amps per output, parallelable for more current.
- 12 VDC Filtered outputs: up to 1.5 amps per output.
- Isolated 24 VAC outputs: up to 2 amps per output.
- AC and DC outputs can be combined in one unit.
- All PTC protected outputs meet Class 2, power limited, requirements
- Line Cord and cam lock are included
- Cabinet dimensions: 12"H x 12"W x 4"D
- UL Listed



### Specifications

#### STANDARD MODELS

AC 4-1-1UL - 4 Outputs, 100 VA, 4.2 Amps, 24 VAC, Fused, UL Listed  
AC 8-1-1UL - 8 Outputs, 100 VA, 4.2 Amps, 24 VAC, Fused, UL Listed  
AC 16-2-1UL - 16 Outputs, 200 VA, 8.4 Amps, 24 VAC, Fused, UL Listed

DCR 4-4-1UL- 4 Outputs, 6 Amps, Regulated, 12 VDC, Fused, UL Listed  
DCR 8-4-1UL- 8 Outputs, 6 Amps, Regulated, 12 VDC, Fused, UL Listed  
DCR 16-8-1-1UL- 16 Outputs, 8.4 Amps, Regulated, 12 VDC, Fused, UL Listed  
DCR 16-12-1UL- 16 Outputs, 12 Amps, Regulated, 12 VDC, Fused, UL Listed

WX10024UL Outdoor, 100VA, 24 VAC, Transformer UL Listed  
(Usage: Indoor or Outdoor Speed Domes, single source, high output)

The above mentioned models have been produced in conformity with the standard for Class 2 Power Units UL1210 and power supplies with extra low voltage Class 2 outputs (C 22.2 No. 223-M91 and UL1012).

Units were tested according to IMN-101298 test programs.

Specifications subject to change without notice.

2025 Opportunity Drive #1 Roseville, CA 95678  
Toll free - (888) 771-4544 ● Phone - (916) 787-1100 ● Fax - (916) 787-1010  
sales@armelectronics.com ● www.armelectronics.com

**ARM  
ELECTRONICS**